



## 20W LED H80 Lamp - 5000K

Item # 665

L20H80/50K

1 LAMP SPECIFICATION							
1-1	Lamp Type	LED H80					
1-2	Dimmable (Y/N)	NO					
1-3	Base	E26					
1-4	Lamp Finish/Type	H80					
1-5	Lamp Wattage	20W					
1-6	Wattage Comparison (FC on Floor)	250 Incand. (55W CFL)					
1-7	Rated Average Life (hours) L70	50,000					
1-8	LED Type	48 X 0.40W SMD					
1-9	Reliable Operating Temperature	-4F to 113F					
2 Photometric Characteristics							
2-1	Initial Lumens	2700					
2-2	Centre Beam Candle Power (Cd)	605					
2-3	Beam Angle (50% I Max) in Degree	140					
2-4	Beam Angle (10% I Max) in Degree	220					
2-5	Initial Lumens per Watt	135					
2-6	Color Temperature	5000K					
2-7	Color Rendering Index (CRI)	>80					
3 Electrical Characteristics							
3-1	Input Line Voltage/Frequency	120V/277V 50/60 Hz		3-2	Power Factor	>0.90	
3-3	Lamp rated Wattage	20W		3-4	Input Line Current	180mA(120V) 80mA(277V)	
3-5	Total Harmonic Distortion	<30%(120V), <20% (277V)		3-6	Dimming Range in %	Not Dimmable	
4 Dimensional Characteristics							
4-1	Nominal Length (Inches/mm)	6.69" / 170 mm		4-2	Diameter	3.15" / 80 mm	
5 Product Information							
5-1	Description	20W LED H80 Lamp - 5000K					
5-2	Primary Application	Commercial, Industrial, Agriculture					
5-3	Warranty	5 Years from date of purchase					
5-4	TCLP Compliant	YES		5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N)	LM79		5-8	ETL- ( Wet Loctaion)	YES	
6 PACKING DETAILS							
6-1	Color Box Size (cm)	1x1	8.5 X 8.5 X 18.6		6-2	Inner Carton Size (cm)	N/A
6-3	Master Carton Size (cm)	1x12	35.5 X 27 X 20	Gross Weight ( Kg)	5.5	Net Weight ( Kg)	3.60
12/2016© Overdrive				ETL CLASSIFIED 			
For more information visit <a href="http://www.overdrive-lighting.com">www.overdrive-lighting.com</a>							

Note: This document is property of "OVERDRIVE Electronics Pvt. Ltd" and should not be copied or distributed without written permission.  
 This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.