



# 6W LED A Bulb Dimmable - 3000K/5000K Wet Location with Gasket

**Item # 731/732**  
**L6SA19DIM/30K-50K**

1 LAMP SPECIFICATION			
1-1	Lamp Type	LED A Bulb Dimmable	
1-2	Dimmable (Y/N)	YES	
1-3	Base	E26 (Medium Base)	
1-4	Lamp Finish/Type	A19 Shape	
1-5	Lamp Wattage	6W	
1-6	Wattage Comparison (FC on Floor)	60W Incand	
1-7	Rated Average Life (hours) L70	25,000	
1-8	Reliable Operating Temperature	-4F to 113F	
1-9	Wet Location Rated	YES	
1-10	Enclosed Fixture Rated	YES	
2 Photometric Characteristics			
2-1	Initial Lumens	545/560	
2-2	Centre Beam Candle Power (Cd)	145	
2-3	Beam Angle (50% I Max) in Degree	125	
2-4	Beam Angle (10% I Max) in Degree	200	
2-5	Initial Lumens per Watt	91	
2-6	Color Temperature	3000K/5000K	
2-7	Color Rendering Index (CRI)	>80	
3 Electrical Characteristics			
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2 Power Factor >0.90
3-3	Lamp rated Wattage	6W	3-4 Input Line Current 55mA
3-5	Total Harmonic Distortion	20%	3-6 Dimming Range in % Full
4 Dimensional Characteristics			
4-1	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2 Diameter 2.36" / 60 mm
5 Product Information			
5-1	Description	6W LED A Bulb Dimmable, 3000K/5000K, Medium Base - Wet location with Gasket	
5-2	Primary Application	Household Use, Office, Agriculture & Commercial	
5-3	Warranty	5 Years from date of purchase	
5-4	TCLP Compliant	YES	5-6 RoHS Compliant YES
5-5	Energy Star or LM79 (Y/N)	LM79	5-8 UL / FCC YES
6 PACKING DETAILS			
6-1	Color Box Size (Inches)	1x1 2.44 x 2.44 x 4.72	6-2 Inner Carton Size (cm) 1x12 10.35 x 7.72 x 5.12
6-3	Master Carton Size (Inches)	1x48 16.50 x 11.14 x 11.81	6-4 Gross Weight / Net Weight ( lbs ) 12.08 / 7.50



10/2020© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

*Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.*