



6.5W LED A19 AG Lamp - 2700K-5000K (Non Dim) Wet Location with Gasket

Item # 790G/791G

L6SNA19/27K-50K

1 LAMP SPECIFICATION

1-1	Lamp Type	LED A19 Lamp
1-2	Dimmable (Y/N)	No
1-3	Base	E26 (Medium Base)
1-4	Lamp Finish/Type	A19 Shape
1-5	Lamp Wattage	6.5W
1-6	Wattage Comparison	60W Incand.
1-7	Rated Average Life (hours) L70	25,000
1-8	Reliable Operating Temperature	-4F to 113F
1-9	Wet Location Rated	YES
1-10	Enclosed Fixture Rated	YES



2 Photometric Characteristics

2-1	Initial Lumens	630
2-2	Centre Beam Candle Power (Cd)	160
2-3	Beam Angle (50%) in Degree	125
2-4	Beam Angle (10% I Max) in Degree	210
2-5	Initial Lumens per Watt	97
2-6	Color Temperature	2700K/5000K
2-7	Color Rendering Index (CRI)	80



3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	>0.80
3-3	Lamp rated Wattage	6.5W	3-4	Input Line Current	70mA
3-5	Total Harmonic Distortion	55%	3-6	Dimming Range in %	No

4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	4.25 Inch / 108mm	4-2	Diameter	2.36 inch/60mm
-----	----------------------------	-------------------	-----	----------	----------------

5 Product Information

5-1	Description	6.5W LED A19 AG Lamp, 2700K/5000K Medium Base - Non Dim With Gasket			
5-2	Primary Application	Household Use, Office, Agriculture & Commercial			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant LM79 only	YES
5-5	Energy Star or LM79 (Y/N)	5-7	UL / FCC		YES

6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	2.44 x 2.44 x 4.72	6-2	Inner Carton Size (cm)	1x12	10.35 x 7.72 x 5.12
6-3	Master Carton Size (Inches)	1x48	16.50 x 11.14 x 11.81	6-4	Gross Weight / Net Weight (lbs)		11.88 / 7.28

10/2020© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.